



CLEANFIX

Cleaning adhesive promoter for applying reactive resin coatings.

Coverage

25 g/m²

Drying time

2–3 minutes (23°C)

Pack sizes

1 L • 5 L

DESCRIPTION

CLEANFIX is an adhesion promoter for ceramic and marble substrates, to be used prior to applying specific reactive resin coatings, enabling direct adhesion. Thanks to its dual activating and degreasing action, it dry-cleans away general dirt residues and common contaminants, providing a reliable bonding base.

The combined preparatory and cleaning action can, in certain cases, avoid both invasive mechanical preparation that generates dust and the use of the anchoring primers normally required, simplifying the application cycle and reducing working time.

The formulation is designed for use both indoors and outdoors.

INTENDED USE

CLEANFIX is intended for preparing and cleaning ceramic and marble surfaces prior to the application of reactive resin coatings in general, including acrylic, epoxy, polyurethane and alkyd systems.

Removal of general surface dirt and residues that may compromise adhesion.

For applications where you want to avoid both invasive preparation and the use of a primer, while still ensuring adhesion of specific finishing resin coatings.

Suitable for floors and wall coverings, both indoors and outdoors.

CLEANFIX is compatible with the following Naici coatings:

- LO SMALTONE PIASTRELLE E CEMENTO ● TRAFFICO
- MATÈRIKA ● PRÀTIKA ● NAIRETAN 200 H ● NAIRETAN 200 HP
- NAIRETAN 200 ● NAIRETAN 200 POLIURETANICO/P
- NAIRETAN FOOD/P

BENEFITS

- Fewer working steps: In certain cases, it removes the need for invasive mechanical preparation and the specified bonding primer.
- Improved adhesion of reactive coatings: optimises substrate preparation by enhancing surface compatibility.
- Cleaning performance: removes the most common dirt and residues that hinder adhesion.
- Lower overall system costs: fewer processing steps, more cost-effective application.

This data sheet is based on our best knowledge of the product. As we cannot exercise any control over its application and as there are numerous variables in use, NAICI accepts no responsibility for the use of the product. Always refer to the latest updated version of the technical data sheet, available at naici.it, or contact ufficiotecnico@naici.it

INSTRUCTIONS FOR USE

Substrate quality

The substrate must be sound and stable, free from efflorescence, moisture, industrial oils and greases, lime and cement residues, any loose or flaking parts, and previous treatments that could impair adhesion of the subsequent coating.

Product preparation

The product is ready to use.

Material application

Dampen a cloth with the product and wipe it over the surface until it has evaporated. Before applying the next finishing coat, wait around 1 hour to allow complete evaporation, observing a maximum limit of 12 hours and avoiding contact with water, rainfall and humidity.

TECHNICAL DATA

PRODUCT DATA	
Type	activating cleaner
Appearance	clear liquid
VOC	Directive 2004/42/EC: FIXING PRIMERS (BS). EU limit value for this product (cat. A/h): 750 g/L. CLEANFIX contains max. 750 g/L of VOC
Storage	12 months from the production date when stored in the original packaging, in a dry place at a temperature between +5 and +35 °C
APPLICATION DATA	
Specific gravity	0.8 g/cm ³
Consumption	25 g/m ²
Application temperature	from +5 °C to 35 °C
Drying time (23°C - RH 60-65%)	2–3 minutes
ADHESION	
TILES AND MARBLE	
Enamelled tiles and concrete	2.3 MPa
Foot traffic	1.9 MPa
Matèrika	2.5 MPa
Pràtika	2.5 MPa
Nairetan 200 H	3 MPa
Nairetan 200 HP	2.5 MPa
Nairetan 200	3 MPa
Nairetan 200 Polyurethane/P	2.5 MPa
Nairetan Food/P	3 MPa

This data sheet is based on our best knowledge of the product. As we have no control over how it is applied and there are many possible conditions of use, NAICI accepts no liability for the product's use. Always refer to the latest updated version of the technical data sheet, available at naici.it, or contact ufficiotecnico@naici.it



PACK SIZES

1 L • 5 L

WARNINGS

Ensure areas are well ventilated during use.

If there are grout joints between tiles, avoid soaking them with CLEANFIX to prevent issues caused by product evaporation.

After application, prevent any contact with water, rain or damp, as this will impair the product's properties.

Use only on approved substrates and with the specified finishing coatings.

When using the product, wear protective gloves and safety goggles, and take all necessary precautions.

For further, comprehensive information on safe use of the product, it is recommended that you consult the latest version of the safety data sheet.

Always check the latest updated version of the technical data sheet.

Under no circumstances add water to the product.

SPECIFICATION CLAUSE

Preparation of low- or non-absorbent ceramic or marble substrates by applying the surface preparation product CLEANFIX (Naici) with a cloth, with an average coverage of around 25 g/m². Thanks to its dual activating and degreasing action, it removes everyday dirt residues and enables direct adhesion of reactive resin coatings of an acrylic, epoxy, polyurethane and alkyd nature.

This data sheet is based on our best knowledge of the product. As we cannot exercise any control over how it is applied, and as there are many possible ways it may be used, NAICI accepts no responsibility for the use of the product. Always refer to the latest updated version of the technical data sheet, available at naici.it, or contact ufficiotecnico@naici.it

