



FIX


Acrylic wall fixative with a consolidating action.

Colour
Milky

Average coverage
up to 30 m²/L
(depending on dilution and the type of substrate)

Pack sizes
1 L • 5 L • 25 L

APPLICATION



DESCRIPTION

FIX is a concentrated wall fixative based on high-quality styrene-acrylic resins in aqueous dispersion. Its high resin content, anti-mould properties and excellent penetration make it ideal for preparing surfaces prior to painting with water-based paints (washable paints, quartz paints, distempers, etc.). As well as re-consolidating the substrate, FIX creates an optimal bonding layer on the surface it is applied to, evening out absorption and therefore improving workability, adhesion and the finish of the subsequent coat. Suitable for both interior and exterior use, on new or existing walls.

INTENDED USE

FIX is used as an adhesion promoter before applying water-based paints (washable paints, quartz paints, distempers, etc.).

BENEFITS

- Anti-mould
- Excellent penetration
- Creates an excellent bonding layer

HOW TO USE

Surface preparation

The surface to be treated must be thoroughly clean and free from any loose or flaking areas. Any dust on the surface should be removed either dry or with water. New plaster must be fully cured.

Product preparation

FIX must be diluted with water, bearing in mind that up to 6 L of water can be added to 1 L of FIX. Use less water when applying to highly absorbent surfaces.

Application

Apply using a brush, roller or spray and allow it to dry; depending on the ambient temperature, this will take around 6–8 hours, after which you can proceed with the desired finish.

TECHNICAL DATA

PRODUCT DATA	
Colour	milky
Appearance	liquid
Density	1,035 kg/L $\pm$ 0,2
Water solubility	soluble
pH	>8
Flammability	non-flammable
VOC	Directive 2004/42/EC Binding primers (BA). EU limit value for this product (cat. A/h): 30 g/L. Fix contains 10 g/L VOC
Shelf life	24 months at temperatures between +5°C and +35°C, away from moisture
APPLICATION DATA	
Coverage	up to 30 m ² /L depending on dilution and the product's absorption
Application temperature limits	+5°C to +35°C
Drying time	6–8 hours
Tool cleaning	with water

PACK SIZES

1 L • 5 L • 25 L

WARNINGS

Do not apply at temperatures below +5 °C.

Do not apply to hot surfaces or surfaces exposed to direct sunlight.

Store in a dry place at a temperature between +5 °C and +35 °C.

When using, wear gloves and protective goggles, and take all necessary precautions.

For further, complete information on safe use of the product, please refer to the latest version of the safety data sheet.

Eye irritant. In case of contact, rinse thoroughly with water and, if necessary, seek medical advice.

Use latex gloves.

Keep out of reach of children.

Do not dispose of the container in the environment after use.

SPECIFICATION CLAUSE

Priming and consolidation of masonry surfaces to be coated with water-based paints, by applying the acrylic fixative known as FIX – Naici – suitably diluted according to the type of surface and its level of absorbency, and applied by brush or roller before painting.

This data sheet is based on our best current knowledge of the product. As we cannot control how it is applied and as conditions of use may vary, NAICI accepts no liability for the use of the product. Always refer to the latest updated version of the technical data sheet, available at naici.it, or contact ufficiotecnico@naici.it

