



PRIMER DARK/S

Solvent-based bitumen primer for laying bituminous membranes.

Colour

Black

Average consumption

150-300 g/m²

Packs

5 L • 10 L • 18 L

APPLICATION



DESCRIPTION

PRIMER DARK/S is an emulsion of selected bitumens and fast-drying resins with excellent wetting power which, unlike standard bituminous primers, not only promotes adhesion but also provides a consolidating effect thanks to its high resin content.

INTENDED USE

PRIMER DARK/S is used as a consolidating bituminous primer before applying any bituminous membrane. It is suitable for applying new waterproofing treatments over existing bituminous membranes because the solvent it contains slightly softens the surface of the old coating, helping the new layer to bond properly. Ideal for concrete structures.

ADVANTAGES

- Easy to apply
- Ready to use
- Exceptional adhesion

APPLICATION INSTRUCTIONS

Substrate preparation

Thoroughly clean the substrate, taking care to remove any loose material, oils, grease and anything else that could impair proper adhesion of the product. Apply to dry surfaces only.

Product preparation

PRIMER DARK/S is ready to use. Stir thoroughly before application.

Application

Apply PRIMER DARK/S in a single coat using a roller, airless sprayer, brush or broom.

TECHNICAL DATA

PRODUCT DATA	
Appearance	liquid
Colour	black
Density UNI EN ISO 8310	0.83 ± 0.05 g/cm ³
VOC	DIR 2004/42/EC Fixative primers (BS). EU limit value for this product (cat. A/h): 750 g/L. PRIMER DARK/S contains 600 g/L VOC
Storage	12 months from the production date, when stored in original packaging, in a dry place away from heat sources, moisture and frost, at a temperature between +5 and +35 °C
APPLICATION DATA	
Drying time	30 minutes at 25°C
Operating temperature range	+ 5°C + 30°C
Dry residue UNI 8309	40%±5
Minimum application temperature	+5°C
Coverage	150-300 g/m ²

PACK SIZES

5 L • 10 L • 18 L

This data sheet is based on our best knowledge of the product. As we have no control over how it is applied, and as there are many possible conditions of use, NAICI accepts no liability for the use of the product. Always refer to the latest updated version of the technical data sheet, available at naici.it, or contact ufficiotecnico@naici.it

WARNINGS

The substrate to be treated must be properly prepared, and be perfectly sound and dry. Do not apply at temperatures other than those stated in the technical data. Store the product in dry areas, away from heat sources.

When using, wear gloves and safety goggles, and take all necessary precautions.

For further, comprehensive information on safe use of the product, please consult the latest version of the safety data sheet.

The substrate to be treated must be properly prepared, and be perfectly sound and dry.

Do not apply at temperatures other than those stated in the technical data.

Store the product in dry premises and away from heat sources.

HAZARD STATEMENTS

H225 Highly flammable liquid and vapour.

H361d Suspected of damaging the unborn child.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P331 DO NOT induce vomiting.

P280 Wear protective gloves/protective clothing and protect eyes/face.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor/...

P370+P378 In case of fire: use ... to extinguish.

P273 Avoid release to the environment.

Contains: TOLUENE, XYLENE, STYRENE, ETHYL ACETATE.

SPECIFICATION CLAUSE

Priming of the surface to be waterproofed, using a consolidating bonding primer based on an emulsion of selected bitumens and fast-drying resins, such as PRIMER DARK/S – NAICI, with an average consumption of 150–300 g/m².

This data sheet is based on our best knowledge of the product. As we cannot exercise any control over its application and, given the many possible variations in use, NAICI accepts no liability for how the product is used. Always refer to the latest updated version of the technical data sheet, available at naici.it, or contact ufficiotecnico@naici.it

