



SALVATORE TRASPARENTE

Clear waterproof protective treatment for terraces and balconies.

Packs

Clear

Packs

- protective kit for approx. 15 m²
- protective kit for approx. 75 m²

DESCRIPTION

SALVATORE TRASPARENTE (applied in a 1st and 2nd coat) is a clear waterproof protective treatment based on specialised, innovative resins. It is designed to resolve seepage caused by "micro-cracking" (<1 mm) on tiled terraces and balconies. Most leaks occur due to the high absorbency of the materials or the presence of tiny cracks in the tiles or grout lines.

APPLICATION



INTENDED USE

Thanks to its water-repellent action, SALVATORE Transparent stops seepage caused by these issues on virtually all types of tiles—terracotta, porcelain stoneware, clinker, stone and cement—widely used for terrace and balcony flooring. SALVATORE Transparent also provides excellent substrate consolidation while preserving natural breathability.

- Salvatore Trasparente 1st coat (impregnating) is an impregnating product based on specialised, innovative resins dissolved in solvents. It must be applied before Salvatore Transparent 2nd coat (finish).
- Salvatore Trasparente 2nd coat (finish) is an impregnating product based on specialised, innovative resins dissolved in solvents. It must be applied after Salvatore Transparent 1st coat (impregnating).

ADVANTAGES

- Easy to apply
- Supplied as a kit
- Ready to use
- Excellent consolidating action on the substrate

This data sheet is based on our best knowledge of the product. As we cannot exercise any control over its application and since there are many possible variations in use, NAICI accepts no liability for the use of the product. Always refer to the latest updated version of the technical data sheet, available on naici.it, or contact ufficiotecnico@naici.it

HOW TO USE

Substrate preparation

The surface must be sound and completely clean of any dirt (grease, dust, etc.), free from loose or flaking parts, and dry. If any moisture is present, wait for it to evaporate and for the surface to be fully dry.

Application

SALVATORE Transparent is ready to use.

▪ SALVATORE TRASPARENTE 1st coat (impregnating coat)

Pour the product into a clean glass or metal container. Apply evenly across the entire surface, working in cross passes and taking care to thoroughly saturate grout lines and any cracks. Avoid leaving excess product on non-absorbent surfaces. Allow 20 minutes for drying; meanwhile, return any unused product to the container and clean the tray and roller with absorbent paper or a dry cloth.

▪ SALVATORE TRASPARENTE 2nd coat (finish)

Pour the product into a clean glass or metal container. Apply evenly across the entire surface, working in cross passes and taking care to thoroughly saturate grout lines and any cracks. Avoid leaving excess product on non-absorbent surfaces. Allow 20 minutes for drying; meanwhile, return any unused product to the container and clean the tray and roller with absorbent paper or a dry cloth.

Consumption

With 1 L of SALVATORE TRASPARENTE 1st coat + 1 L of SALVATORE TRASPARENTE 2nd coat, you can typically protect 10/15 m² of surface area.

Coverage may vary slightly depending on the surface absorbency, the tile size and the existing grout joints.

TECHNICAL DATA

PRODUCT DATA	
Appearance	liquid
Density, 1st coat	0,82 g/cm ³ ±0,05
Density, 2nd coat	0,84 g/cm ³ ±0,05
Shelf life	1 year at a temperature between +5 and +30 °C, away from moisture
APPLICATION DATA	
Coverage	• 1L first coat + 1L second coat for 10/15 m² • 5L first coat + 5L second coat for 75 m²
Surface drying time	1 hour at 23 °C
Full cure	1 day
Contact angle	>125 degrees
Service temperature limits	+ 5°C / + 35° C
Tool cleaning	immediately with solvent

This data sheet is based on our best knowledge of the product. As we cannot exercise any control over how it is applied, and as conditions and methods of use may vary, NAICI accepts no liability for the use of the product. Always refer to the latest updated version of the technical data sheet, available at naici.it, or contact ufficiotecnico@naici.it



PACKAGING

- Protective kit for 15 m² (1L impregnant + 1L finish)
- Protective kit for 75 m² (5L impregnant + 5L finish)

WARNINGS

Make sure there is no sediment in the bucket, mixing thoroughly. For best results, avoid applying during the hottest hours of the day.

Do not allow rain to fall on the product during the first day after application.

This product is flammable. During application, protect your airways, eyes and skin.

When using the product, wear protective gloves and safety goggles, and take all necessary precautions.

For further, comprehensive guidance on safe use of the product, please consult the latest version of the Safety Data Sheet.

The treatment carried out with SALVATORE TRASPARENTE does not replace waterproofing work performed with liquid membranes where these are required; it must therefore be used only for permitted applications, following a careful assessment of the substrate.